



Aluminum Sound Columns TS-C/TS-A 300/500/700/1000

Type	Power (Watt)	Dimensions (mm)	SPL P max/1m (dB)	SPL 1W/1m (dB)	Frequency Range (Hz)	Dispersion angle
TS-A 10-300/T	10/6/3/1.5	344x99x72	103.3	93.3	150 - 18,000	232° (h) 140° (v)
TS-A 20-500/T	20/15/10/5	500x100x72	110.4	97.3	200- 19,000	360° (h) 90° (v)
TS-A 30-700/T	30/15/7.5	715x99x72	107.7	92.9	150 - 13,000	230° (h) 56° (v)
TS-A 30-700/T plus	30/15/7.5	715x99x72	109.5	94.7	150 - 23,000	230° (h) 148° (v)
TS-A 50-1000/T	50/30/15/7.5	986x99x72	110.7	93.7	150 - 17,000	244° (h) 62° (v)
TS-A 50-1000/T plus	50/30/15/7.5	986x99 x72	111.1	94.1	150 - 21,000	154° (h) 106° (v)
TS-C 10-300/T	10/6/3/1.5	344x100x92	103.3	93.3	150 - 18,000	232° (h) 140° (v)
TS-C 30-700/T	30/15/7.5	700x100x92	107.7	92.9	150 - 13,000	230° (h) 56° (v)
TS-C 30-700/T plus	30/15/7.5	700x100x92	109.5	94.7	150 - 23,000	230° (h) 148° (v)
TS-C 50-1000/T	50/30/15/7.5	971x100x92	110.7	93.7	150 - 17,000	244° (h) 62° (v)
TS-C 50-1000/T plus	50/30/15/7.5	971x100x92	111.1	94.1	150 - 21,000	154° (h) 106° (v)
TS-SH	-	150x70x100	-	-	-	-
TS-BS 880	-	h.max = 1,88	-	-	-	-